

Mesh Banner Gloss M1 340

matt 8216 - 340 g/m²

Glossy, wind permeable mesh (M1 flame retardant) of PVC coated, polyester base fabric with release liner designed for solvent and UV-curable printing.

Advantages

- Large advertisements, Scaffolds, banner. Release liner
- Light, tear resistant
- Weldable, dimensional stable
- Flame retardant M1/ B1

Storage conditions

Shelf life: 2 years. Store cool and dry, free from direct sunlight. It is recommended to cover the material with polythene sheets for protection against dust and humidity.

Print Conditions

Best results are obtained between 15-25°C and 35-65% RH.

Environment, Health & Safety

No material safety datasheet required.

Outdoor use

The material has a lifetime of up to three years. A gradual fading is common and depending on the quality of the ink.

Lamination

Compatibility

Hot	Warm	Cold
1	1	1
3=excellent	2= fair	1= not recommended

Hot: heat activated: 105°C - 130°C

Warm: heat activated: 85°C - 95°C

Cold: pressure sensitive

Colour Profiles

Sihl Direct b.v. develops high quality colour profiles for media / ink / printer / Rip combinations.

Check availability of profiles for your printer at the download section www.sihl.nl or contact us at +31(0)73-6441044.

ING Bank 's-Bosch 67.47.92.742
BTW NL805593445B01
IBAN NL97 INGB 0674 7927 42
BIC/SWIFTCODE INGBNL2A

Op al onze aanbiedingen en overeenkomsten zijn de ICT-Office Voorwaarden van toepassing, gedeponeerd d.d. 14 januari 2009 bij de Kamer van Koophandel te Midden-Nederland onder nummer 30174840. De afnemer heeft van deze voorwaarden kennis genomen en verklaart zich akkoord met de inhoud van deze voorwaarden. Op verzoek worden de ICT-Office Voorwaarden kosteloos nogmaals toegezonden.

Sihl Direct bv
Mangaan 8
5234 GD 's-HERTOGENBOSCH

telefoon +31(0)73 6441044
telefax +31(0)73 6441212
e-mail sihl@sihl.nl
internet www.sihl.nl
K.v.K. 's-Bosch 160.55.676

Mesh Banner Gloss M1 340

matt 8216 - 340 g/m²

List of Printers

Printer	Ink	Quality
Océ CS6060/6100	Solvent	Excellent
Océ CS9065/9090 (low solvent)	Solvent	Excellent
Océ CS9065/9090 (eco solvent)	Solvent	Excellent
Océ CS7070/7075/7100	Solvent	Excellent
Océ Arizona series	Solvent	Excellent
Seiko color painter 64S / 100S	Solvent	Excellent
HP Designjet 8000s/9000s/10000s	Solvent	Excellent
Mutoh rockhopper (eco solvent ultra)	Solvent	Excellent
Mutoh spitfire (mild solvent)	Solvent	Excellent
Mutoh Toucan/Osprey/Phoenix	Solvent	Excellent
Agfa grand sherpa	Solvent	Excellent
ColorSpan display maker 72/98 UVX/UVR	Solvent	Excellent
ColorSpan display maker 72s/98s	Solvent	Excellent
Gandiinnovations Jeti 33xx/5000	Solvent	Excellent
Mimaki JV3 series	Solvent	Excellent
Roland Soljet/Versacam series	Solvent	Excellent
NUR, Scitex, Vutek	Solvent	Excellent

ING Bank 's-Bosch 67.47.92.742
BTW NL805593445B01
IBAN NL97 INGB 0674 7927 42
BIC/SWIFTCODE INGBNL2A

Op al onze aanbiedingen en overeenkomsten zijn de ICT-Office Voorwaarden van toepassing, gedeponereerd d.d. 14 januari 2009 bij de Kamer van Koophandel te Midden-Nederland onder nummer 30174840. De afnemer heeft van deze voorwaarden kennis genomen en verklaart zich akkoord met de inhoud van deze voorwaarden. Op verzoek worden de ICT-Office Voorwaarden kosteloos nogmaals toegezonden.

Sihl Direct bv
Mangaan 8
5234 GD 's-HERTOGENBOSCH

telefoon +31(0)73 6441044
telefax +31(0)73 6441212
e-mail sihl@sihl.nl
internet www.sihl.nl
K.v.K. 's-Bosch 160.55.676

Mesh Banner Gloss M1 340**matt 8216 - 340 g/m²****Physical Properties**

Weight	340 g/m ²	DIN 53855	Tear strength: warp	> 300 N	DIN 53363
Thickness	400 µm	DIN 53854	Tear strength: weft	> 150 N	DIN 53363
Tensile strength: warp	> 2100 N/5cm	DIN 53857	Elongation: warp	20%	DIN 53857
Tensile strength: weft	> 1600 N/5cm	DIN 53857	Elongation: weft	20%	DIN 53857
Temperature Stability	-20 - 70°C		Flammability (tested without backing paper)	M1/B1	NF P92- 503
Dimensional Stability	< 0,5 %				/DIN4102

Available widths (mm)

3"Core 1372 1600 2500

The data provided in this product data sheet are values for orientation only.

Before using our print media please check their suitability for your printer and for your intended application. We do not take any liability for failures or damages resulting from technically modified printing inks and/or printers as technical specifications are subject to change.

ING Bank 's-Bosch 67.47.92.742
 BTW NL805593445B01
 IBAN NL97 INGB 0674 7927 42
 BIC/SWIFTCODE INGBNL2A

Op al onze aanbiedingen en overeenkomsten zijn de ICT-Office Voorwaarden van toepassing, gedeponereerd d.d. 14 januari 2009 bij de Kamer van Koophandel te Midden-Nederland onder nummer 30174840. De afnemer heeft van deze voorwaarden kennis genomen en verklaart zich akkoord met de inhoud van deze voorwaarden. Op verzoek worden de ICT-Office Voorwaarden kosteloos nogmaals toegezonden.

Sihl Direct bv
 Mangaan 8
 5234 GD 's-HERTOGENBOSCH

telefoon +31(0)73 6441044
 telefax +31(0)73 6441212
 e-mail sihl@sihl.nl
 internet www.sihl.nl
 K.v.K. 's-Bosch 160.55.676