

Classic Window Film Perforated 200

matt 8570 - 200 µm

Perforated (1.5 mm perforation), flexible pressure-sensitive, exterior-mount film for solvent and UV- curable inks. The film has a bright white printing surface, a black adhesive side and 2 release liners.

Advantages

- Vehicle graphics, transit advertising, shopping centers
- One way visibility
- Small perforations allow detail and text, easy application and removal
- Reduces heat and glare from the sun

Storage conditions

Shelf life: 1 year, temperature 10-30°C, relative humidity 30 - 70%. Repack opened rolls when not in use. Allow material to adapt to room conditions for 24 hours before printing.

Print Conditions

Best results are obtained between 20°C and 35-70% RH.

Environment, Health & Safety

No material safety datasheet required. Waste not suitable for recycling.

Outdoor use

This material is developed for outdoor use. Expected lifetime exterior two to three years. (-17°C to 60°C) Six months for clean removal. Adhesion will increase with time.

Lamination

Compatibility

Hot	Warm	Cold
1	1	3*
3=excellent	2= fair	1= not recommended
* use special laminates DOL4000 or DOL4100		

Hot: heat activated: 105°C - 130°C
Warm: heat activated: 85°C - 95°C
Cold: pressure sensitive

Colour Profiles

Sihl Direct b.v. develops high quality colour profiles for media / ink / printer / Rip combinations. Check availability of profiles for your printer at the download section www.sihl.nl or contact us at +31(0)73-6441044.

Classic Window Film Perforated 200

matt 8570 - 200 µm

List of Printers

Printer	Ink	Quality
Océ CS6060/6100	Solvent	Excellent
Océ CS9065/9090 (low solvent)	Solvent	Excellent
Océ CS9065/9090 (eco solvent)	Solvent	Excellent
Océ CS7070/7075/7100	Solvent	Excellent
Océ Arizona series	Solvent	Excellent
Seiko color painter 64S / 100S	Solvent	Excellent
HP Designjet 8000s/9000s/10000s	Solvent	Excellent
Mutoh rockhopper (eco solvent ultra)	Solvent	Excellent
Mutoh spitfire (mild solvent)	Solvent	Excellent
Mutoh Toucan/Osprey/Phoenix	Solvent	Excellent
Agfa grand sherpa	Solvent	Excellent
ColorSpan display maker 72/98 UVX/UVR	Solvent	Excellent
ColorSpan display maker 72s/98s	Solvent	Excellent
Gandiinnovations Jeti 33xx/5000	Solvent	Excellent
Mimaki JV3 series	Solvent	Excellent
Roland Soljet/Versacam series	Solvent	Excellent
NUR, Scitex, Vutek	Solvent	Excellent

ING Bank 's-Bosch 67.47.92.742
 BTW NL805593445B01
 IBAN NL97 INGB 0674 7927 42
 BIC/SWIFTCODE INGBNL2A

Op al onze aanbiedingen en overeenkomsten zijn de ICT-Office Voorwaarden van toepassing, gedeponereerd d.d. 14 januari 2009 bij de Kamer van Koophandel te Midden-Nederland onder nummer 30174840. De afnemer heeft van deze voorwaarden kennis genomen en verklaart zich akkoord met de inhoud van deze voorwaarden. Op verzoek worden de ICT-Office Voorwaarden kosteloos nogmaals toegezonden.

Sihl Direct bv
 Mangaan 8
 5234 GD 's-HERTOGENBOSCH

telefoon +31(0)73 6441044
 telefax +31(0)73 6441212
 e-mail sihl@sihl.nl
 internet www.sihl.nl
 K.v.K. 's-Bosch 160.55.676

Solvent PVC

Classic Window Film Perforated 200

matt 8570 - 200 µm

Physical Properties

Total Thickness	440 µm	Perforation size	1,5 mm
Vinyl Thickness	200 µm	Open area	50%

Available widths (mm)

3"Core

1372

The data provided in this product data sheet are values for orientation only.

Before using our print media please check their suitability for your printer and for your intended application. We do not take any liability for failures or damages resulting from technically modified printing inks and/or printers as technical specifications are subject to change.

ING Bank 's-Bosch 67.47.92.742
BTW NL805593445B01
IBAN NL97 INGB 0674 7927 42
BIC/SWIFTCODE INGBNL2A

Op al onze aanbiedingen en overeenkomsten zijn de ICT-Office Voorwaarden van toepassing, gedeponereerd d.d. 14 januari 2009 bij de Kamer van Koophandel te Midden-Nederland onder nummer 30174840. De afnemer heeft van deze voorwaarden kennis genomen en verklaart zich akkoord met de inhoud van deze voorwaarden. Op verzoek worden de ICT-Office Voorwaarden kosteloos nogmaals toegezonden.

Sihl Direct bv
Mangaan 8
5234 GD 's-HERTOGENBOSCH

telefoon +31(0)73 6441044
telefax +31(0)73 6441212
e-mail sihl@sihl.nl
internet www.sihl.nl
K.v.K. 's-Bosch 160.55.676